



Nitrile

Durable protection in a comfortable, versatile glove

- Versatile disposable glove ideal for a wide variety of industrial applications
- Textured throughout the palm to ensure good grip in wet, dry and oily environment
- Silicone-free for better product protection
- Tested for use with chemotherapy drugs



Industries

- Automotive
- Chemical
- Machinery and Equipment
- Life Sciences
- Food Processing

Recommended For

- Assembly and inspection of components
- Light assembly tasks
- Handling of paint/glue guns and sprayers
- Chemical Handling
- Cleaning of plant and machines
- Blending, compounding materials
- Equipment repair and maintenance
- Handling of tools
- Maintenance
- Laboratory analysis
- Transferring liquids and solids
- Sample taking and processing
- Food processing and handling



TECHNICAL DATA SHEET

| Product Information | |
|-------------------------------------|---|
| External Glove Surface | Fully Textured |
| Audit Standards | ISO 13485, ISO 9001 |
| Product Certification | Medical Device Regulation (EU) 2017/745 Class I, Personal Protective Equipment Regulation (EU) 2016/425 Category III risks |
| Packaging Overview | 100 gloves per dispenser 10 dispensers per case 1000 gloves per case |
| Storage Instructions | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin | Malaysia |
| Product Segmentation | Multi-Purpose |
| Antistatic | Yes |
| Vulcanization Chemical Accelerators | <ul style="list-style-type: none"> Zinc Dibutyldithiocarbamate (ZDBC) Zinc Diethyldithiocarbamate (ZDEC) <p><i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i></p> |


PHYSICAL PROPERTIES

| | Typical Values | | Testing Method |
|---|---------------------|--------------------|----------------------|
| Length (mm/inches) | 240 / 9.5 | | ASTM D3767, EN 420 |
| Freedom from Holes (Inspection level I) | 1.5 AQL | | ASTM D5151, EN 374-2 |
| Palm Thickness (mm/mils) | 0.11 / 4.3 | | ASTM D3767, EN 420 |
| Finger Thickness (mm/mils) | 0.12 / 4.7 | | ASTM D3767, EN 420 |
| | BEFORE AGING | AFTER AGING | |
| Ultimate Tensile Strength (MPa) | 22 | 14 | ASTM D412 & D573 |
| Elongation at Break (%) | 500 | 400 | ASTM D412 |
| Force at break (N) | 6 | 6 | EN 455-2 |

ORDERING INFORMATION

| Size | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) |
|--------------|--------------|-------------|-------------|-------------|---------------|
| Product Code | 93143060 | 93143070 | 93143080 | 93143090 | 931430100 |

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region

Ansell Global Trading Center
(Malaysia) Sdn Bhd
T: +603 8310 6688
F: +603 8310 6699

North America Region

Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.
T: +52 442 248 1544 / 248 3133

Australia

Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia

Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; www.ansell.com/patentmarking © 2022 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

